



# Hawai'i Natural Energy Institute Research Highlights

## Electrochemical Power Systems

### Materials Enablers for Advanced Manufacturing of Attritable Fuel Cells

**OBJECTIVE AND SIGNIFICANCE:** Hydrogen fuel cell systems are ideally suited to power small unmanned systems that will be increasingly important when competing against near-peer adversaries. A key facet of small unmanned systems is their attritability relative to expensive weapons systems. Attritable fuel cell-powered unmanned systems require that the cost of fuel cells (FC) decrease so that their loss is acceptable in an exchange. This cost decrease can be traded against durability and performance, but ideally, both performance and durability would remain relatively constant. This is a uniquely DoD problem whose materials challenges are not being addressed by the broader fuel cell industry or academia. The objective of this project is to perform material research combined with simulation to propose a conceptual design for a fuel cell with laminate construction to realize a 5x cost decrease over state-of-the-art small FCs (0.5-5 kW) while retaining performance.

**BACKGROUND:** Hydrogen FCs have the potential to be a disruptive technology for energy storage and power production for the DoD. Their ability to store energy efficiently, produce electric power with low signature, and operate with minimum maintenance provide an important compliment to battery electric systems and internal combustion engines. Hydrogen FCs' key advantages over the incumbent technologies are 4-8x gravimetric energy storage density over batteries, which translates into 4-8x endurance/range for systems and low signature DC power with improved start times over internal combustion engines. Key technical challenges remain for hydrogen FCs, namely cost, heat rejection, and volumetric storage density of hydrogen as compared to logistic fuels.

A large fraction of cost of system fabrication for small-scale FCs is associated with the bipolar plates and the labor costs associated with building the device because of the large part count. The objective of this work is to move FC manufacturing closer to battery manufacturing, in which continuous reel-to-reel process are used to manufacture the electrode, which are then rolled or stacked into containers that require very little handwork or parts registration.

**PROJECT STATUS/RESULTS:** Under this work, HNEI is investigating the potential of high temperature proton exchange membrane fuel cells (HT-PEM) to develop materials enablers that will allow for the construction of FCs with cheaper assembly costs through a simpler system architecture to reduce components. HT-PEM also has the potential to reduce the costs of precious metal catalysts and polymer membrane substrates to achieve the target cost reduction. The higher operating temperatures of HT-PEM directly addresses heat rejection challenges through higher temperature operation (120-200° C). Volumetric storage challenges of hydrogen are indirectly addressed in this project through a simpler FC system architecture and increased heat rejection that leads to volume savings in the FC system that can be applied to hydrogen storage space claim.

This project began in Fall 2022. Initial efforts underway focus on integration of thin mesh metallic current collectors into fuel cell electrodes.

*Funding Source:* Office of Naval Research

*Contact:* Keith Bethune, [bethune@hawaii.edu](mailto:bethune@hawaii.edu)

*Last Updated:* October 2022

